

524519

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



11 FEB 2005



(43) International Publication Date  
18 March 2004 (18.03.2004)

PCT

(10) International Publication Number  
**WO 2004/022239 A1**

(51) International Patent Classification<sup>7</sup>: **B04B 9/00 //**  
F01M 13/04, B01D 45/14

ELIASSON, Thomas [SE/SE]; Hyltingevägen 29, S-125  
40 Älvsjö (SE).

(21) International Application Number:  
PCT/SE2003/001334

(74) Agent: **CLIVEMO, Ingemar**; Alfa Laval Corporate AB,  
Hans Stahles väg, S-147 80 Tumba (SE).

(22) International Filing Date: 28 August 2003 (28.08.2003)

(81) Designated States (*national*): AE, AG, AL, AM, AT (uti-  
lity model), AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA,  
CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (uti-  
lity model), DE, DK (utility model), DK, DM, DZ, EC, EE  
(utility model), EE, ES, FI (utility model), FI, GB, GD, GE,  
GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ,  
LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN,  
MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO,  
RU, SC, SD, SE, SG, SK (utility model), SK, SL, SY, TJ,  
TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA,  
ZM, ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
0202622.7 4 September 2002 (04.09.2002) SE

(71) Applicant (*for all designated States except US*): **ALFA  
LAVAL CORPORATE AB** [SE/SE]; Box 73, S-221 00  
Lund (SE).


(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **HÄLLGREN, In-  
gvar** [SE/SE]; Solbacksvägen 26, S-147 41 Tumba (SE).

(84) Designated States (*regional*): ARIPO patent (GH, GM,  
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),  
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

[Continued on next page]

(54) Title: AN APPARATUS FOR CLEANING OF GAS



(57) **Abstract:** In an apparatus for cleaning of gases a centrifugal rotor (7) is supported by two bearings, in which it is rotatable about a rotational axis. The two bearings are lubricated by means of an oil mist, which is generated in a space (6), when oil is sprayed against a turbine wheel (22) supported by the rotor. Whereas the bearing (9), which is situated nearest said space (6), is lubricated by oil mist present in the space, the second bearing (8) is lubricated by oil mist being conducted to it through a central channel (11) in the centrifugal rotor.

WO 2004/022239 A1